

Product Description

AutoMax is synthetic technology automatic transmission fluid developed to provide excellent wear protection for transmissions required Dexron III standard. It provides superior heat and oxidation resistance to deliver sludge control, plus optimize proper frictional characteristic for avoiding harsh shifting.

Characteristics

- Recommended for all models of automatic transmission required DEXRON III, MERCON or below.
- Suitable for power steering fluid.

Benefits

- Improves fuel consumption and provides good seal compatibility.
- Gives smoothly start and better speed acceleration.
- Construction or mining equipment
- Reduces engine wear and extends gear life.
- Provides smoothly and precisely gear change.

Typical Characteristics

TEST	METHODS	UNITS	RESULTS
Density at (15 °C)	ASTM D 4052	g/cm ³	0.848
Kinematic Viscosity 40 °C	ASTM D 445	mm ² /s	37.1
Kinematic Viscosity 100 °C	ASTM D 445	mm ² /s	7.47
Viscosity Index	ASTM D 2270		180
Flash Point	ASTM D 92	°C	220
Pour Point	ASTM D 5950	°C	-51

Health & Safety

There is no such significant health or safety hazard when used under the recommended application and suitable handling.

Avoid the direct contact. Wash Immediately After contact. Health and safety information is available on the Safety Data Sheet (SDS).